

SONHA

ALL IN ONE HEAT PUMP

80%

**ENERGY
SAVINGS**



Website



LinkedIn



SON HA INTERNATIONAL CORPORATION

13th Floor, Capital Place, No. 29 Lieu Giai Street, Ngoc Ha Ward, Hanoi, Vietnam

SPECIFICATIONS

Tank capacity	270L
Refrigerant type/charge	R290/450g
Rated power input (heatpump)	958W
Total power input (heatpump + backup heater)	1992W
Heating capacity output (heatpump)	2650W
Coefficient of performance (COP)	5.4
Rated voltage/frequency	220-240V~, 50Hz
Rated current (heatpump)	4.1A
Total rated current	8.7A
Max. suction side pressure	0.95MPa
Max. discharge side pressure	3.1MPa
Default set temperature	60°C
Noise level	42dB (A)
Net weight (Kg)	114kg
Dimensions (mm)	653x1880 mm
Waterproof rating	IPX4



MICRO-CHANNEL HEAT EXCHANGE TECHNOLOGY
Enhanced heat transfer & faster heating



HIGH-EFFICIENCY INVERTER COMPRESSOR
Fast heating - Stable - Durable



PREMIUM ENAMEL-COATED INSULATED TANK
Superior corrosion resistance - Up to 96 hours of heat retention



SILENTCORE TECHNOLOGY
Multi-layer sound insulation & optimized anti - Vibration design



INTERGRATED DESIGN
Compact & Space - Saving - Easy installation



SMART TOUCH CONTROL
Premium - Minimalist - Modern



ECO-FRIENDLY
High-efficiency R290 refrigerant for energy saving

